



2017/1/12

Brandon

Brand	PLANET	PLANET
Model	BSP-360	BSP-300
Product Image		
Level	Managed	Unmanaged
Hardware Specification		
Network Connector	5-Port RJ45 for 10/100/1000BASE-T (4-Port with 802.3at / 802.3af PoE)	3-Port RJ45 for 10/100/1000BASE-T (2-Port with 802.3at / 802.3af PoE)
Power Output	2 DC 24@ 1A maximum	1 DC 24@ 1A maximum
USB	1 (Type A female)	-
Alarm	1 Digital Output (DO)	-
Console Port	-	1 RS-232 RJ45 serial port
Reset button	1	-
Enclosure	IP30 aluminum case	IP30 case
Installation	DIN Rail Kit and Wall Mount Kit	DIN Rail Kit and Wall Mount Kit
Dimension (W x D x H)	84 x 107 x 152 mm	65 x 107 x 152 mm
Operating Temperature	-10 ~ 60 degrees C	-20 ~ 60 degrees C
Power over Ethernet		
PoE Standard	802.3af/at	802.3af/at
PoE 802.3af Port	4	2
PoE 802.3at Port	4	2
PoE Power Output	PoE out 51VDC; max. 30 watts per PoE	PoE out 51VDC; max. 30 watts per PoE
PoE Budget	120 watts max. (depends on power input)	60 watts max. (depends on power input)
PSE Type	End-Span	End-Span
Power Pin Assignment	1/2(+), 3/6(-)	1/2(+), 3/6(-)
Battery Management		
Battery Current Usage and Status	■ (Web)	■ (Console Port)
Battery Capacity Statistics	■ (Web)	■ (Console Port)
(LVD) Low Voltage Disconnection	■ (Web)	■ (Console Port)
Low Voltage Cut-off for PoE Port	■ (Web)	-
Pulse Width Modulation (PWM)	■	■
PD Management		
PoE Usage Monitoring	■	-
PoE Limit/Total Limit	■	-
PD Alive Check	■	-
Scheduled Power Recycling	■	-
PoE Schedule	■	-